



HORSEMEN

HORSEMEN WOOD CARE
WOOD PROTECTION

ENVIRONMENTALLY FRIENDLY IMPREGNATING AGENT FOR UNTREATED INDOOR AND OUTDOOR WOOD BASED ON THE FINNISH COOKED PAINT TRADITION

HORSEMEN WOOD CARE Wood protection is a water-based wood stain made using natural raw materials combined with natural waxes. It's ideal for treating all untreated garden wood, wooden chalets or houses, cladding, fences, pergolas, carports, etc. It is a 100% natural stain, based on a 300-year-old Finnish tradition combined with our newly developed wax technology!

By applying this wood stain, the wood is protected naturally; the wood can continue to breathe so the stain can never flake, and your wood gets a rustic, matte look with excellent water resistance. The extremely small wax particles, combined with the natural oils and pigment give your wood years of protection with respect for nature!

APPLICATION

- Chalets, wooden houses, cladding, garden fences, nesting boxes, wooden carports, wooden outbuildings, garden sheds, wooden garden toys, etc.
- The wood **MUST** be untreated to apply this wood stain!
- Allow impregnated wood to saturate for six months before treating.

FEATURES

- Good penetration due to the thin viscosity
- Breathable protection that makes cedar wood easy to maintain over time.
- The product is 100% VOC-free and based on natural raw materials.
- Post treatment requires only dusting and can be treated again without sanding.
- Vapour-permeable;
- Safe for wood, people and the environment.
- Follows a 300-year tradition.
- Makes cedar naturally water and dirt repellent.
- Odourless.

TECHNICAL INFORMATION

- Density: 1.2
- Scent: light oil scent
- Viscosity: 20"/DIN 4 mm.
- Shelf life: 2 years in closed package.
- Appearance: coloured liquid.

HANDLING

Stir well before use and let sit for a few minutes. Use only on new, untreated cedar wood. Dust the wood beforehand. Apply undiluted with a wide block brush. Can also be sprayed using airless or airmix method. Clean used materials with water.

DRYING TIME

Dry to the touch after about 60 minutes depending on the surface and weather conditions. Wait at least 24 hours before applying a second coat.

USE

5 m² per litre, depending on the application method and the absorption level of the wood. The second layer requires less. We still recommend applying at least two coats on new wood.

PACKAGING AND STOCKING

Available packaging: 2500 ml. can
Shelf life: 2 years in closed package.
Keep out of reach of children and protected from frost.

SAFETY

This product is completely safe for people and the environment. It is classified as harmless and contains 0 grams of solvent.

The data described in the technical data sheet have been compiled based on the necessary tests and years of experience. The user must test the application of the product in question in the light of the current and existing conditions. No guarantee can be derived from the technical data sheet. If in doubt, carry out a test first.

