



HORSEMEN

HORSEMEN DECK CARE
GARDEN WOOD
PROTECTION

ENVIRONMENTALLY FRIENDLY IMPREGNATING AGENT FOR UNTREATED EXOTIC WOOD, THERMOWOOD, ACCOYA, IMPREGNATED WOOD, CEDAR.

HORSEMEN DECK CARE GARDEN WOOD PROTECTION provides water-based water and dirt protection for untreated exotic wood, thermally treated wood such as thermowood and accoya and pressure impregnated wood. It also provides excellent protection for composite wood.

Working with these new developments, we can protect against water, algae and air pollution with a guarantee of easy maintenance. The extremely small wax particles, in combination with natural oils and high-quality pigments in HORSEMEN DECK CARE GARDEN WOOD PROTECTION, ensure penetration into the pore of the wood and form a breathable, water-repellent and dirt-repellent protective layer. Cleaning and maintenance is much easier. Because the pores of the wood are filled with wax, algae and moss can no longer adhere to the wood.

APPLICATION

- Exotic hardwood such as teak, bankraai, ifte, paddock, afzelia (should never be finished with a filming agent!)
- Primarily recommended for cedar wood, which becomes black instead of grey due to air and other pollution.
- The product offers protection for untreated wood used on terraces, garden furniture, cladding, decking, wooden gates, etc.

FEATURES

- Good penetration thanks to the minuscule wax emulsion.
- After it dries, the surface retains its original colour!
- The pores of the wood are filled with natural waxes so algae and moss cannot adhere to the wood.
- Protects against rainwater, air pollution and other pollution.
- Boasts anti-bacterial properties and is completely vapour permeable.
- Contains no silicone oil or solvents (0 grams VOC).
- Easy to apply.
- Safe for people, the environment and stone.
- Does not stain other materials (drops and puddles can be wiped away).
- After a few months, the wood will turn grey but will no longer get dirty, creating even, natural weathering.
- Protects your surface against pollution, water and algae
- A high return on maintenance costs; pressure washing is no longer necessary, which means your wood will have a longer life.
- A durable treatment that greatly reduces maintenance frequency.

EFFECT

After evaporation of the water, the treated surface will be covered with a natural wax layer that acts as a water and dirt repellent. We recommend treating at least twice to ensure that all pores are filled. The product is at its best after 24 hours of drying at a maximum relative humidity of 60%. The layers must be applied evenly. There is no discolouration of the wood and the gloss of the surface does not change. For very strongly absorbing surfaces (old wood), it may be necessary to continue treating until the surface is completely saturated.

TECHNICAL INFORMATION

- Density: 1
- pH value: 9.4
- Scent: light wax scent
- Viscosity: 16"/DIN. 4 mm
- Appearance: milky liquid

HANDLING

Shake well before use and let sit for a few minutes. Apply to clean, degreased surfaces. If there is moss or algae on the wood, first remove them with a suitable moss remover or cleaner and let dry. Note: for very absorbent surfaces, do not apply too much at once, as it could leave a white haze after drying. Always continue applying in separate layers until the surface is saturated.

APPLICATION

Apply undiluted with a brush or roller. For larger surfaces, the product can be applied with a low-pressure sprayer; afterwards, continue to distribute the applied product evenly with a brush or roller. It is also possible to apply the product via an airless sprayer, but be sure to distribute the product evenly again afterwards. Avoid puddles and drops and if they occur, brush them out well.

Never apply to surfaces that are too warm (in full sun) because the water will evaporate too quickly, causing the product to dry too quickly, meaning it can no longer be distributed evenly (to prevent streaking). All materials used can be cleaned with water.

DRYING TIME

Dry to the touch after about 60 minutes, depending on the surface and weather conditions. Allow the product to harden for at least 24 hours before placing anything on the surface!

USE

5 to 10 m² per litre depending on the application method and the absorption level of the wood. With a second coat, only half of the recommended amount is needed, and optimal performance is achieved when the surface is fully saturated.

PACKAGING AND STOCKING

Available packaging: 1 litre spray cans, 5 litre jerry can.
Shelf life: max. 2 years in closed package
Storage: out of reach of children and away from frost.

SAFETY

This product is completely safe for people and the environment. The preparation is classified as harmless and contains 0 grams of solvent.

The data described in the technical data sheet have been compiled based on the necessary tests and years of experience. The user must test the application of the product in question in the light of the current and existing conditions. No guarantee can be derived from the technical data sheet. If in doubt, carry out a test first.

